




CREATE A STRIKING CUSTOM SHOWPIECE FROM THE FLOOR UP USING HURFORD HERRINGBONE ENGINEERED PARQUET FLOORING.

Each block of Hurford Herringbone is carefully constructed using a prime grade Oak lamella for the wear layer, which is bonded to a strong Eucalyptus plywood core and reinforced with a veneer backing. This type of construction ensures product stability and the highest level of quality assurance.





ADD A CUSTOMISED STAIN AND FINISH.

Hurford Herringbone has been produced leaving an unfinished, uncoated RAW surface. RAW is the ideal selection to achieve a custom design vision, with limitless choices of stains and finishes to reflect one's personal taste or style.



Specifications...

| | |
|----------------------------|---|
| Species: | Oak |
| Colour Stains: | RAW (unfinished) |
| Appearance: | Prime |
| Core Material: | Plantation Eucalyptus Plywood |
| Locking System: | Tongue and Groove (ends and sides) |
| Profile: | Square edge (ends and sides) |
| Size: | 120mm x 14mm |
| Wear Layer: | 3mm lamella |
| Length: | 600mm |
| Surface: | Smooth, lightly sanded |
| Coating: | Uncoated |
| Finish: | Unfinished |
| Coverage: | 1.728M ² /box |
| Packaging: | 24 pieces per box |
| Install Suitability: | Direct glued |
| Install Sub-Floor Heating: | Yes |
| Install Over: | Wood, concrete, plywood & plywood over concrete |
| Colour Match Accessories: | N/A |

Installing Hurford Herringbone requires a high level of skill and Hurford Flooring recommends only qualified tradespeople with the relevant skill levels undertake the installation.

Hurford Herringbone is sold as an uncoated, unfinished product. Stains listed are for illustrative purposes.

