

**PRONTO**  
READY TO GO

PLANK & PARQUETRY

*Hi-Spec  
Visual Grade*  
*Less knots, cleaner look*



 by  
**PREFERENCE**  
FLOORS



Parchment

#### ENGINEERED FOR QUALITY

- Multiply construction, Tongue & Groove
- Grade ABC. Janka hardness 5,5 – 6.0kN
- Tongue & Groove
- Micro bevel 4 sides
- Light brushed surface
- VOC free water based matte coating E1
- Fire Test, CHF 3.5 kW/m<sup>2</sup> & Smoke Value 26% minutes. Slip Test P3
- T&G stair nosing available
- Suitable for hydronic in-slab heating only

#### WIDE PLANK:

- 1900mm set length with nested shorts
- 190 x 14/3mm, 2.166m<sup>2</sup>/Ctn

#### HERRINGBONE:

- 600mm length 120 x 14/3mm, 0.864m<sup>2</sup>/Ctn

25 Year Limited (Lifetime) Structural Warranty  
20 Years Limited Residential Coating Warranty  
5 Years Limited Commercial Structural & Wear Warranty

## *Hi-Spec Visual Grade*

*Less knots, cleaner look.*


Pronto engineered oak planks & parquetry are manufactured using a Hi-Spec Visual A/B/C grade with the 3mm solid oak wear layer bonded directly to an 11mm structural multi-layer plywood substrate. This trusted method of manufacturing provides a dimensionally stable and durable floor with an eye-catching aesthetic for a cleaner, sharper look. Finished thickness of 14mm. Pronto wide planks are presented with a Tongue & Groove (T&G) profile for direct stick or a floating method of installation.

**Parquetry (T&G) profile must be direct fix install only.**

**Pronto is all about speed and efficiency with the cost conscious consumer in mind.**

With a tight palette of light to dark colours the range is designed to maximise quality without compromising the performance of the product. Pronto ready to go, ideally suited for residential or multi-residential living.

**Wide Plank**  
 Size: 1900mm  
 (nested shorts)  
 190 x 14/3  
 2.166m<sup>2</sup>/Ctn



*\*Images for illustrative purposes only, batch and grade variations will occur.*



Chesterfield



Dockside



Misty Cove



Parchment



River Sand



Seafoam




Washed Pebble



Welsh Slate

**Herringbone**  
 Size: 600mm  
 120 x 14/3  
 0.864m<sup>2</sup>/Ctn  
 Direct fix only



*\*Images for illustrative purposes only, batch and grade variations will occur.*




Chesterfield



Misty Cove



Parchment



Seafoam



Washed Pebble



## STAIR NOSING ACCESSORIES

Tongue & Groove stair nosing is available to support our range of Engineered Oak products.

Stair nosing can be supplied directly from Preference Floors to suit your colour selection or a Reseller may supply directly from a manufacturer to suit local building regulations.

If stairs are involved in your project it is wise to spend time discussing this matter prior to purchase.

*\*These images are for illustrative purposes only.*



T&G Stair Nosing

## TRIMS & SCOTIA

An extensive range of Scotia colours and Aluminium floor trims are available. These elements form an integral part of all floor installations and especially when floating installations are required.

As per our warranty guidelines, all floating installations will require perimeter expansion and transition trims. It is wise to spend time discussing trim requirements prior to purchase. Some example images below.



Reducer



U Channel



Expansion / Transition

## Methods of engineered plank construction lay-up

The manufacturing of engineered flooring is designed to be more resource efficient using up to 2/3rds less of our valuable Oak resource when compared to solid timber floors.

Pre-finished Engineered flooring is dimensionally more stable than solid timber flooring enabling quicker installation with less site related trades to complete the flooring installation.

Multi-ply construction has proven to be a highly reliable method of engineered plank construction delivering uniform stability and dimensional accuracy. These attributes speed up the installation process providing the precision required for modern interior fit-outs.

### Multi-ply

Provides a core usually manufactured from mixed hardwood with each veneer (approx. 2mm) running in an alternate direction to provide enhanced radial and longitudinal stability. The wear layer of solid oak is then bonded to the top of the multi-ply core.



Parchment